

Topping Spreader TS 5000

Ensuring accurate and even application of dryshake topping with the TS500 Topping Spreader. Combining high productivity and operator comfort with the latest technological adaptations to provide an emission compliant machine to the latest and Stage V emission level standards.

Ultimate efficiency in dryshake application

Advantages

- Accurate application of dryshake
- Increased productivity
- Spreader head – in/out movement
- Automatic mode for easy operation
- Large material capacity
- Standard parts/components
- Easy to transport by container/lorry
- Touchscreen control
- Individual operator access codes
- Easy to maintain and service
- Foam filled wheels
- Automatic throttle
- LCD display



Specifications subject to change without notice Non contractual photo

Technical description

Specifications	
Width	2.2 m
Length	5.2 m
Height	2.46 m
Weight	8000kg
Boom reach	6.3 m
Boom head width	1.8 m
Steering	2-4 wheels / Crab
Transport dimension	Standard
Bin Capacity	2500kg
Head bin capacity	320kg
Slew	360°

Engine	
Brand	HATZ
Model	4H50TICD
Emission compliance	Stage V
Power	49 KW @ 2400 RPM
Torque	240 nm @ 1600 2600 RPM
Fuel	Diesel
Fuel Tank capacity	110L
Oil Tank capacity	100L

Options	
Eco oil	On request
Air compressor	On request
Operator area protection	On request
Anti-dust kit	On request
Seat heating	On request
Spraying system	On request

Features	
Central greasing system	As standard
Seat pneumatic	As standard
Catalytic – DOC	As standard
Diesel particle filter	As standard